

TECHNICAL DATA

TAMPER

BT 80 D



Long lifetime
All around engine protection



High level of reliability
Biggest air filter in the market




Simple operation
Vibration dampened guide handle

Shipping dimensions in m3

BT 80 D

0,268

**Standard Equipment**

- Vibration insulated steering bow
- Self-cleaning air filter housing
- Integrated fuel filter
- Protective engine covering
- Engine shut-down switch integrated in steering handle
- Infinitely variable frequency
- Single point lifting device
- Plastic castor as loading aid
- Semi-automatic decompression
- Recoil starter
- 3-2-1 Warranty

Optional Equipment

- Transport device with puncture proof wheels
- Tamper foot widths (280-290mm)
- Tool kit
- Service Kit
- TOUGH WARRANTY

Dimensions in mm

	B	H	L	L1	W
BT 80 D	350	1000	765	335	330

Technical Data**BOMAG****BT 80 D****Weights**

Operating weight CECE	kg	81
Basic weight	kg	80

Dimensions

Working width (tamper plate)	mm	330
------------------------------------	----	-----

Driving Characteristics

Working speed max.	m/min	16
-------------------------	-------	----

Drive

Engine manufacturer		Yanmar
Type		L 48
Emission stage		non EPA
Cooling		air
Number of cylinders		1
Performance ISO 3046	kW	3,1
Speed	min-1	3.600
Fuel		Diesel
Drive system		mech.
Fuel consump. aver. during operation	l/h	0,7

Exciter system

Frequency	Hz	8-11,5
Impact force	kN	17,5

Capacities

Fuel	l	3,0
------------	---	-----

Technical modifications reserved. Machines may be shown with options.



PRE 540 54 010

040219 Sa01

BOMAG
 Hellerwald
 D-56154 Boppard
 P.O. Box 5162
 Tel. (0)6742 - 1000
 Fax (0)6742 - 3090

