


# TECHNICAL DATA

TANDEM ROLLERS

BW 80 AD-5, BW 90 AD-5, BW 100 ADM-5





#### Dimensions in mm

	A	B	C	D	H	H2	K	L	O	S	W
BW 80 AD-5	1483	856	433	580	1627	2304	255	2194	28	13	800
BW 90 AD-5	1483	956	433	580	1627	2304	255	2194	28	12	900
BW 100 ADM-5	1483	1056	433	580	1627	2304	255	2194	28	12	1000

#### Shipping dimensions in m3

BW 80 AD-5  
 BW 90 AD-5  
 BW 100 ADM-5

#### without ROPS

3,056  
 3,413  
 3,770

#### with ROPS

4,327  
 4,833  
 5,338

Machine type	Compaction output (m3/h) at recommended soil layer thicknesses		
	Gravel, sand	Mixed soil	Silt, clay
BW 80 AD-5	60-110	42-85	33-65
BW 90 AD-5	70-120	45-90	35-70
BW 100 ADM-5	75-140	50-100	36-70

Machine type	Compaction output (t/h) at different asphalt layer thicknesses		
	2-4 cm	6-8 cm	10-14 cm
BW 80 AD-5	10-30	25-45	35-70
BW 90 AD-5	15-30	30-50	40-80
BW 100 ADM-5	15-40	35-60	50-90

Technical Data		BOMAG BW 80 AD-5	BOMAG BW 90 AD-5	BOMAG BW 100 ADM-5
<b>Weights</b>				
Operating weight CECE .....	kg	1.550	1.600	1.700
Average static linear load CECE .....	kg/cm	9,7	8,9	8,5
Grossweight .....	kg	1.900	1.900	1.900
<b>Dimensions</b>				
Working width .....	mm	800	900	1.000
Track radius, inner .....	mm	2.080	2.030	1.980
<b>Driving Characteristics</b>				
Speed .....	km/h	0- 10,0	0- 10,0	0- 10,0
Working speed with vibration .....	km/h	0- 10,0	0- 10,0	0- 10,0
Max. gradeability without/with vibr. ....	%	40/30	40/30	40/30
<b>Drive</b>				
Engine manufacturer .....		Kubota	Kubota	Kubota
Type .....		D 902	D 902	D 902
Emission stage .....		Stage V / TIER4f	Stage V / TIER4f	Stage V / TIER4f
Cooling .....		water	water	water
Number of cylinders .....		3	3	3
Performance ISO 14396 .....	kW	15,1	15,1	15,1
Performance SAE J 1995 .....	hp	20,2	20,2	20,2
Speed .....	min-1	3.000	3.000	3.000
Speed adjustment 1 .....		2.100	2.100	2.100
Speed adjustment 2 .....		3.000	3.000	3.000
Electric equipment .....	V	12	12	12
Driven drum .....		front + rear	front + rear	front + rear
<b>Brakes</b>				
Service brake .....		hydraul.	hydraul.	hydraul.
Parking brake .....		hydromec.	hydromec.	hydromec.
<b>Steering</b>				
Steering system .....		oscl.artic.	oscl.artic.	oscl.artic.
Steering method .....		hydraul.	hydraul.	hydraul.
Steering / oscillating angle +/- .....	grad	33/8	33/8	33/8
Crab walk .....	mm	0- 50	0- 50	0- 50
<b>Exciter system</b>				
Vibrating drum .....		front + rear	front + rear	front + rear
Drive system .....		hydraul.	hydraul.	hydraul.
Frequency .....	Hz	42/63	42/63	42/63
Amplitude .....	mm	0,50	0,50	0,40
Centrifugal force .....	kl	7/17	8/17	8/17
<b>Sprinkler System</b>				
Type of sprinkling .....		pressure	pressure	pressure
<b>Capacities</b>				
Fuel .....	l	30,0	30,0	30,0
Water .....	l	100,0	100,0	100,0

Technical modifications reserved. Machines may be shown with options.

### Standard Equipment

- Hydrostatic travel and vibration drive
- Travel drive in series
- 2 scrapers per drum, spring loaded and tiltable
- Pressure sprinkler system with interval switch
- Multi function travel lever
- Multi-function display incl. operating hour meter
- Water level
- Emergency STOP
- Individual control, vibration
- Intelligent Vibration Control (IVC)
- Integrated storage compartment
- Adjustable operator's seat
- Seat contact switch
- Vandalism protection
- 12V socket
- Working lights front and rear
- Back-up alarm
- Lashing eyes, galvanized
- Single point lifting device
- Lockable engine hood made of composite material

### Optional Equipment

- ROPS with safety belt
- \* Foldable ROPS incl. seat belt
- Double travel lever
- Seat heating
- ECONOMIZER with asphalt temperature display
- Temperature display
- BOMAG TELEMATIC
- Theft protection
- Indicator and hazard lights
- Rotary beacon
- Optional lighting on ROPS
- Battery disconnect switch
- Environmentally compliant hydraulic oil
- Special painting
- Edge cutter
- Port for hydraulic breaker
- Backup warning buzzer with broadband technology
- ECOSTOP
- Outside mirrors
- Tablet holder set

\* Standard delivery with CE conformity  
(valid within European Union)

