

DIAMOND SAW BLADES

WET CUTTING for concrete saws

WITTHAUT



ASPHALT - segmented, soldered

TYPE ANH / ANS



with core protecting segments (TCT-segments)



with declining core protecting segments



ø inches	Application:
12" (300 mm) ↓ 48" (1200 mm)	asphalt, bituminous floors partially suited for: floor pavement, concrete with abrasive aggregates, sandstone, chamotte
12" (300 mm) ↓ 24" (600 mm)	

CONCRETE - segmented, soldered

TYPE - BN




ø inches	Application:
12" (300 mm) ↓ 48" (1200 mm)	cured concrete, ferroconcrete partially suited for: aerated concrete, slag concrete

WET CUTTING for table saws and construction saws



SPECIAL EXECUTION - segmented, soldered

WIDE SLOTS



SMALL SLOTS



ø inches	Special bonds for cutting of:
8" (200 mm) ↓ 100" (2500 mm)	Type FNH - green concrete, 12" - 48" (300 - 1200 mm) Type DNH - asphalt over concrete, 12" - 48" (300 - 1200 mm) Type RT - fireclay, refractories, 12" - 24" (300 - 600 mm) Type QT - masonry stones, 12" - 20" (300 - 500 mm)
8" (200 mm) ↓ 48" (1200 mm)	Type XT - hard bricks, 12" - 20" (300 - 500 mm) Type GT - granite, porphyry, 4" - 48" (105 - 1200 mm) Type GSE - granite, porphyry (silent core), 4" - 48" (105 - 600 mm) Type MT - marble, 4" - 48" (105 - 1200 mm) Type MSE - marble (silent core), 4" - 24" (105 - 600 mm)

Specifications for further materials upon request !